



AGM WATERTRUCKS

4000gal • 2450gal

PRODUCT DESCRIPTION

Controlled Water Distribution Systems For Today's Environment. Dust Control with Limited Availability of Water Supplies

KEY FEATURES

- Interior Epoxy Coating: The interior of the AGM tank is epoxy coated for extended tank life.
- Water Pump PTO Driven: AGM utilizes a Berkley B3 water pump capable of 650 GPM at 50 PSI.
- Ground Level Fill: Twin discharge pipes into fill port from ground fill connection with air gap.
- Water Cannon: High quality, stainless steel, AGM electric/pneumatic water cannon, spraying up to 75 feet from unit.
- Hydrant Fill Connection: To fill the AGM tank from a hydrant, connect 3 inch ground level connection provided.
- Front Bumper Sprays: Two independently operated spray heads mounted on front bumper of unit.
- Power Dump Bar: Injects water at high pressure for penetration into soil to provide adequate moisture for compaction.
- Hose Reel: Hose reel with 50 feet of 1 inch hose and nozzle for hand watering.
- Side Spray: Top of tank mounted side spray (adjustable) for spraying burms, ditches, and piles.
- In-Cab Electronic Controls: Allows for individual control of all 5 spray heads, plus joy stick control for water cannon.
- Rear Spray Heads: Two independently operated spray heads mounted at rear of tank for dust control.



4000gal on FL 6x6



2450gal on FL 4x4



Rear View



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date

08/11/08