



BRINDLE POLE TRAILER

PT10T • PT15TG • PT30TG

PT10TG

- GVWR: 10,000lb
- Tires: 235/85 16E Duals
- Frame: 5" Channel
- Overall Width: 90"
- Bolster: 5" Channel
- Bolster Length: 87"
- Trailer Weight: 2,500lb
- Height to Bolster: 42"
- Length of Tongue Extended from Center of Eye to Rear: 35'
- Single Axle



PT10T

PT15TG

- GVWR: 15,000lb
- Tires: 215-75R, 17.5 Duals
- Frame: 5" Channel
- Overall Width: 90"
- Bolster: 5" Channel
- Bolster Length: 87"
- Trailer Weight: 2,700lb
- Height to Bolster: 42"
- Length of Tongue Extended from Center of Eye to Rear: 40'
- Single Axle



PT15TG

PT30TG

- GVWR: 30,000lb
- Tires: 215-75R, 17.5 Duals
- Frame: 5" Channel
- Overall Width: 90"
- Bolster: 5" Channel
- Bolster Length: 87"
- Trailer Weight: 4,800lb
- Height to Bolster: 42"
- Length of Tongue Extended from Center of Eye to Rear: 50'
- Tandem Axle



PT30TG

SHEARED FEATURES

- 2 - Cable Winch Binders
- 1 - Nylon Binder
- 1 - Heavy Duty Stabilizer Jack on Tongue (7,000lb cap Swing Away)
- ICC Lighting
- Electric Brakes with Solar Charging Battery
- 2 - Aluminum Storage Compartments (one per side)
- Optional - Air Brakes with Air Reservoir and Line Kit
- Galvanized Steel - Painted Steel Optional



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date

08/11/08