



HOGG & DAVIS PULLER

ODP 60 Drum Puller

PRODUCT DESCRIPTION

The ODP 60 is a single drum puller capable of line pull or tension of up to 6,000lb. Disengaging the drive system allows for free wheel payout of the pulling rope with an integrated hydraulically controlled overspin brake. The operator controlled post style levelwind allows for even winding of rope.

All unit functions are centrally located at the operators station. Engine gauges including tachometer, oil pressure, temp, fuel, and voltage are all in view. Pulling is controlled with an electric over hydraulic, spring return to neutral joystick allowing for infinite control of line speed and presettable line pull.

KEY FEATURES

- Continuous Linepull Rating: 6,000lb
- Continuous Torque Rating: 174,000in-lb
- Infinitely Variable Speed from 0.0 – 4.2mph

- Rated Diameter: 58"
- Width: 44"
- Rated Rope Capacity: 15,160 feet (3/4" dia)

- 99HP Diesel Engine
- Closed Loop Hydrostatic Hydraulic Drive
- Spring Applied, Hydraulic Release Drive Train Brake
- Mechanical Clutch Drum Engagement
- Standard: Freewheel Disconnect
- 16" Diameter Ventilated Overspin Brake

- 19 Gallon Fuel Capacity
- 29.5 Gallon Hydraulic Oil Capacity
- Hydraulic Boom Levelwind
- Lockable Steel Battery Box
- Baked White Enamel Finish

TRAILER FEATURES

- Tandem 8,000lb Leaf-Sprung Axles
- 17,600lb GVWR
- Electric Trailer Brakes
- (3) Drop-Leg Manual Leveling Jacks
- (4) R17.5 – 16 Ply Rated Tires
- Full Coverage Fenders With Mudflaps
- D.O.T. Trailer Lighting with 7-Wire Connector



ODP 60



Control Panel



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date

08/11/08