



HOGG & DAVIS TENSIONER

OLT 72B Overhead Line Bull-Wheel Tensioner

PRODUCT DESCRIPTION

The OLT 72B Overhead Line Tensioner is designed to install single conductor. The bullwheels are canted as per IEEE specifications to prevent unnecessary twisting of the conductor during installation.

The bullwheels are outfitted with replaceable Diameter Molded segments. Molding of the segments in this manor eliminates the gaps between segments and creates a smooth cable surface. 36" stainless steel disc brakes, with centralized braking controls, allow for precise tensioning of the conductor. Fairleads are adjustable for multiple setups: front to back, left to right to tower, and right to left to tower.

KEY FEATURES

- Multi-groove Bull Wheels Rated at 10,000lb
- Permanently Engraved Control Panel
- Full Hydraulic System Controls and Gauges

- Bullwheel Diameter: 72"
- Lining: 8 Section Molded Urethane
- Groove Diameter: 2-1/2" (3" optional)
- Braking: (4) Hydraulic Discs

- Disc Brake Material: Stainless Steel
- Tension Brake: (2) 36" Diameter on Each Bull Wheel
- Hydraulically Controlled Braking Mechanism
- Charge Pump Actuator w/Rotary Adjustment
- Optional Hydraulic Retarder or Water Cooled Brake System

TAILER FEATURES

- Tandem 7,000lb Leaf-Sprung Axles
- 15,000lb GVWR
- Electric Trailer Brakes
- (3) Drop-Leg Manual Leveling Jacks
- (2) R17.5 – 16 Ply Rated Tires
- Full Coverage Fenders With Mudflaps
- D.O.T. Trailer Lighting with 7-Wire Connector



OLT 72B



Control Panel



Rear View



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date

08/11/08