



# LIFT-ALL MH

## LAHM42

### PRODUCT DESCRIPTION

The LAHM is available in a range of working heights from 42'-7" to 47' (13 M to 14.3 M). This personnel lift comes with an automatic two-speed throttle with manual override as a standard. The LAHM also packs our patented hydraulic load gauge and automatic upper boom hold-down. This material handler also has hydraulic tool outlets at the bucket, a hydraulic bucket rotator, hydraulic winch, hydraulic tilting jib, and a winch control at both the bucket and the base. Tested at 100 KV/AC and rated at 46 KV, this model ensures maximum safety and performance. Please view our LAH/HD model for a similar build.

### KEY FEATURES

- Automatic Two-Speed Throttle with Manual Override
- Hydraulic Bucket Rotator
- Fiberglass Inner Boom Fully Insulated
- Hydraulic Winch Control
- Hydraulic Tool Outlets
- Hydraulic Jib Extension
- Hydraulic Load Gauge
- Tested at 100 KV/AC Rated at 46 KV

### SPECIFICATIONS

- Working Height: 47' (12.8m)
- Single Man Side Hung Bucket: 400lb
- Maximum Horizontal Reach: 34'-11" (10.6m)
- 360° Continuous Rotation



LAHM42-1S on IH 4300



Rear View



3112 E State Rd 124  
Bluffton, IN 46714  
USA

T. 1-800-252-0043  
P. 1-260-824-6340  
F. 1-260-824-6350

nescosales.com  
www.nescosales.com  
An American Company

Effective Date

08/11/08