



LIFT-ALL BUCKET

LAN55-2E • LAN/HD75-2E

LAN55-2E PRODUCT DESCRIPTION

The LAN series is available in a range of working heights from 60' to 70' (14.3 M to 17.1 M). (For lower heights, see our LAN 47-56 model). It comes equipped with a one-handle, full feathering hydraulic control at the bucket. Equipped with patented automatic upper boom holddown. This model is tested at 100 KV/AC and rated at 46 KV.

KEY FEATURES

- Automatic Two-Speed Throttle with Manual Override
- Integral Counterbalance Values
- Automatic Upper Boom Holddown
- 32gal Hydraulic Tank
- Full Length Subframe with Four A-Frame Outriggers
- Tested at 100 KV/AC Rated at 46 KV

SPECIFICATIONS

- Working Height: 60' (18.3m)
- End Hung Bucket: Two Man (2E) 700lb
- Maximum Horizontal Reach: 32'-5" (9.9m)
- 360° Continuous Rotation

LAN/HD75-2E PRODUCT DESCRIPTION

The LAN/HD is available in a range of working heights from 60' to 80' (18.3 M to 24.4 M). The LAN/HD sports a rugged design with a one-handle, full feathering hydraulic control mounted at the bucket. This personnel lift utilizes integral counterbalance valves and a patented automatic upper boom holddown. The LAN/HD is tested at 100 KV/AC and rated at 46 KV.

KEY FEATURES

- Automatic Two-Speed Throttle with Manual Override
- Integral Counterbalance Values
- Automatic Upper Boom Holddown
- 32gal Hydraulic Tank
- Full Length Subframe with Four A-Frame Outriggers
- Tested at 100 KV/AC Rated at 46 KV

SPECIFICATIONS

- Working Height: 80' (24.4m)
- End Hung Bucket: Two Man (2E) 800lb
- Maximum Horizontal Reach: 45'-2" (13.8m)
- 360° Continuous Rotation



LAN55-2E on FL M2106 4X4



LAN/HD75-2E on M2106 4X4



LAN/HD75-2E on IH 7300 4x4



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date

08/11/08