



# LIFT-ALL MH

## LM70 • LM75 • LM75/90 • LM75/110

NO PERMITS NEEDED



LM75-2MS on GT3000HY

### PRODUCT DESCRIPTION

The LM is available in a range of working heights from 51' to 80' (15.5 M to 24.4 M). This material handling unit comes with an automatic two-speed throttle with manual override as a standard. Along with the hydraulic tool outlets at the bucket comes a highly versatile hydraulic winch. We also offer our patented hydraulic load gauge and automatic upper boom holddown as standard.

### LM70 SPECIFICATIONS

- Working Height: 75' (22.9m)
- End & Side Hung Buckets: Two Man 700lb
- Winch Capacity: 2,000lb (907kg)
- Maximum Horizontal Reach: 40'-3" (12.3m)
- 360° Continuous Rotation

### LM75 SPECIFICATIONS

- Working Height: 80' (24.4m)
- End & Side Hung Buckets: Two Man 700lb
- Winch Capacity: 2,000lb (907kg)
- Maximum Horizontal Reach: 42'-9" (13m)
- 360° Continuous Rotation

### KEY FEATURES

- Automatic Two-Speed Throttle with Manual Override
- Hydraulic Tool Outlets at the Bucket
- Hydraulic Bucket Rotator
- Hydraulic Winch
- Hydraulic Tilting Jib
- Hydraulic Load Gauge
- Winch Control at the Bucket
- Automatic Upper Boom Holddown
- Full Length Subframe with Four A-Frame Outriggers

### ELEVATORS

The elevator unit is a standard 90° articulation with dual lift cylinders. The integral counterbalance valves and body mounted lower controls make our elevator unit able to reach greater heights. This unit is able to extend the working height of the LM75 from 80' to 95' and 115'.



LM70-2MS on FL M2106V 4x4



LM75/110-2MS on FL M2106V 6x6



3112 E State Rd 124  
Bluffton, IN 46714  
USA

T. 1-800-252-0043  
P. 1-260-824-6340  
F. 1-260-824-6350

nescosales.com  
www.nescosales.com  
An American Company

Effective Date  
08/27/08