



LIFT-ALL MH

LOM10-55 • LOM15-55

PRODUCT DESCRIPTION

The LOM offers lifting capacities from 400lb to 2,000lb in all non-overcenter positions. The LOM comes standard with our patented automatic upper boom holddown and hydraulic load gauge. Our sturdy full-length subframe with four A-frame outriggers makes this unit a durable, long-lasting investment. The LOM is tested at 100 KV/AC, and is rated at 46 KV.

KEY FEATURES

- Automatic Two-Speed Throttle with Manual Override
- Hydraulic Tool Outlets at the Bucket
- Hydraulic Bucket Rotator
- Hydraulic Winch
- Hydraulic Tilting Jib
- Hydraulic Load Gauge
- Winch Control at the Bucket
- Automatic Upper Boom Holddown
- 32gal Hydraulic Tank
- Full Length Subframe with Four A-Frame Outriggers
- Tested at 100 KV/AC Rated at 46 KV

SPECIFICATIONS

- Working Height: 60' (18.3m)
- Side Hung Bucket: Single Man (1S) 400lb or Two Man (2MS) 700lb
- Winch Capacity: 2,000lb
- 360° Continuous Rotation



LOM10-55-2SM on IH 4300



LOM15-55-2SM on FL



LOM15-55-2SM on GT1600HY



3112 E State Rd 124
Bluffton, IN 46714
USA

T. 1-800-252-0043
P. 1-260-824-6340
F. 1-260-824-6350

nescosales.com
www.nescosales.com
An American Company

Effective Date
08/11/08